



US009411315B2

(12) **United States Patent**
Sawada

(10) **Patent No.:** **US 9,411,315 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **ELECTRONIC DEVICE AND WRISTWATCH**

(56) **References Cited**

(71) Applicant: **CASIO COMPUTER CO., LTD.**,
Shibuya-ku, Tokyo (JP)

U.S. PATENT DOCUMENTS

(72) Inventor: **Makoto Sawada**, Nishi-Tokyo (JP)

5,627,548 A * 5/1997 Woo G01S 19/34
342/352
5,663,735 A * 9/1997 Eshenbach G01S 19/235
342/357.62
6,288,977 B1 * 9/2001 Yoshida G04G 5/002
368/187
6,299,345 B1 * 10/2001 Burnette G04F 10/00
273/237

(73) Assignee: **CASIO COMPUTER CO., LTD.**,
Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(Continued)

(21) Appl. No.: **14/613,184**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Feb. 3, 2015**

JP 2007256159 A 10/2007
JP 2011075541 A 4/2011

(65) **Prior Publication Data**

US 2015/0268636 A1 Sep. 24, 2015

OTHER PUBLICATIONS

Japanese Office Action (and English translation thereof) dated Feb. 4,
2016, issued in counterpart Japanese Application No. 2014-055112.

(30) **Foreign Application Priority Data**

Mar. 18, 2014 (JP) 2014-055112

Primary Examiner — Amy Cohen Johnson

Assistant Examiner — Matthew Powell

(74) *Attorney, Agent, or Firm* — Holtz, Holtz & Volek PC

(51) **Int. Cl.**

G04G 21/04 (2013.01)

G04G 13/02 (2006.01)

G04B 19/06 (2006.01)

G04R 20/02 (2013.01)

G04R 60/10 (2013.01)

G04R 20/08 (2013.01)

(52) **U.S. Cl.**

CPC **G04B 19/065** (2013.01); **G04R 20/02**
(2013.01); **G04R 20/08** (2013.01); **G04R 60/10**
(2013.01)

(58) **Field of Classification Search**

CPC G04R 20/00; G04R 20/02; G04R 20/04;
G04R 20/08; G04R 20/10; G04R 20/16;
G04R 20/22; G04R 20/26; G04R 60/10;
G04B 19/065; G04G 21/04

See application file for complete search history.

ABSTRACT

The present invention includes a wristwatch case provided with a watch glass, a dial plate provided in the wristwatch case, and a timepiece module arranged below the dial plate, and the timepiece module has a first antenna arranged in its one end portion so as to receive a high-frequency radio wave for GPS and a second antenna arranged in the other end portion opposing the first antenna so as to receive a standard time radio wave whose frequency differs from that of a radio wave to be received by the first antenna. Accordingly, radio waves for GPS can be received by the first antenna and standard time radio waves can be received by the second antenna arranged opposing the first antenna.

23 Claims, 12 Drawing Sheets

